





All dimensions are in millimeters (mm)



Recommended Panel Cut-Out



Mounting nut torque (Nm)
Metal shell = 22.0

Note:

1) This picture is generic and for illustrative purposes only, and may show different keying, materials, colour, finish, and contact configuration. Minor shape or feature variations to actual item may be present.

All additional information are documented on the datasheet (See below link or QR Code)
www.lemo.com/pdf/EGL.5K.330.CLA.pdf



Fixed socket, nut fixing



LEMO SA
Chemin des Champs-Courbes 28
1024 Ecublens - SWITZERLAND

Tel. (+41) 21 695 16 00
email : info@lemo.com
www.lemo.com

CD

Drawn	05.12.2023	MARI/ MARI
Checked	05.12.2023	OBAR
Modified	00	05.12.2023/ MARI
 DO NOT SCALE DRAWING		

EGL.5K.330.CLA

The diagram shows the model name 'EGL-5K-330-CLA' with vertical lines connecting each part to its meaning: 'EGL' to 'Model', '5K' to 'Alignment Key', '330' to 'Series', and 'CLA' to 'Insert Config.'. Below 'CLA', there are four more vertical lines pointing to 'Housing', 'Insulator', 'Contact', and 'Variant'.

EGL.5K.330.CLA