


All dimensions are in millimeters (mm)

Alignment Key  
Front View

0°

Insert Configuration  
Rear View

Recommended Panel Cut-Out



Mounting nut torque (Nm)  
Metal shell = 12.0  
Plastic shell = 5.0

**Note:**  
1) This picture is generic and for illustrative purposes only, and may show different keying, materials, colour, finish, and contact configuration. Minor shape or feature variations to actual item may be present.

All additional information are documented on the datasheet (See below link or QR Code)  
[www.lemo.com/pdf/PFG.4B.340.CLLD12.pdf](http://www.lemo.com/pdf/PFG.4B.340.CLLD12.pdf)

Model Alignment Key Series Insert Config. Housing Insulator Contact Collet Type Cable Ø Variant  
**PFG.4B.340.CLLD12**

Datasheet



**Fixed socket, with two nuts, cable collet (back panel mounting)**

Series 4B



**LEMO**

LEMO SA  
Chemin des Champs-Courbes 28  
1024 Ecublens - SWITZERLAND

Tel. (+41 21) 695 16 00  
email : [info@lemo.com](mailto:info@lemo.com)  
[www.lemo.com](http://www.lemo.com)

CD

Drawn	17.12.2024	MARI / MARI
Checked	17.12.2024	OBAR
Modified	00	17.12.2024 / MARI
DO NOT SCALE DRAWING		

**PFG.4B.340.CLLD12**